

EHF POKERS

(Electrical ⚡)



DESCRIPTION

The high frequency poke vibrators (EHF) are installed in a powerful motor sealed in EPOXY resin, which protects it from the vibrations. All models are equipped with a protective system which prevents overheating. The transmission is composed of 10 metres of electric cable and 5 metres of hose reinforced with braided metal. The control panel is a waterlight (IP-52) structure constructed in polyamide with an incorporated switch.



SPECIFICATION

Part Number	Poker Diameter mm	Length Head mm	Hose Length m	VPM	Amplitude	Centrifugal Force (N)	Nominal Current (amp)	Weight (Kg)
EHF 38 / 5	38	360	5	13500	1.5	1500	5	12
EHF 38 / 12	38	360	12	13500	1.5	1500	5	22
EHF 50 / 5	50	410	5	12000	2.8	3500	12	14
EHF 50 / 12	50	410	12	12000	2.8	3500	12	24
EHF 60 / 5	60	416	5	12000	3.3	5500	18	16
EHF 60 / 12	60	416	12	12000	3.3	5500	18	26
EHF 70 / 5	70	405	5	12000	2.5	7000	17	18
EHF 70 / 12	70	405	12	12000	2.5	7000	17	28

Other Sizes Available on Request