

SINGLE BEAM SCREED - ESG01

For Finishing Freshly Poured Concrete HONDA



DESCRIPTION

When finishing concrete slabs, Energy wet screed can fit the demands of every job site with a variety of blade lengths, plus each unit is designed to fit the demands of every operator. Two isolators and specialized lower handle mount design reduce vibration to the operator. The squeeze grip handle is also foldable for easy transport and storage.

- Quick clamp on 4 stroke petrol power unit.
- Lightweight unit features lifting handle for easy transport.
- High production unit for quick and accurate strike-off of concrete slabs with or without the support of grade stakes and forms.
- Fully enclosed exciter for operator production and low maintenance.





HANDLE

EASY TO ATTACH

SPECIFICATION

Model	Part No. Engine Power (Hp) - (kW)		Frequency (Hz)	Max. Compaction Deptch (mm)	Width (mm)	Height (mm)	Length (mm)	Weight (Kg)	
Single beam screed Petrol	ESGUT		Honda / 1.2	83	75	700	440	1040	14.6
	Mod	lel	Part No	. Width (mm)	Height (mm)	Length (mm)	Weight (Kg)		
	1.9m Beam		ESB1	200	100	1900	8		
	3m Beam		ESB3	200	100	3000	12.5		
	4m Be	eam	ESB4	200	100	4000	17		

WWW.ENERGY-AE.UK