

BAR CUTTING - EBC42/52

For Cutting of Rebars
(Electrical ⚡ - 3 Phase)




DESCRIPTION

Built according to yard requirement, this machine have three reduction gears increasing the shearing power with a minor consumption of energy. The axial gears in forged and processed steel and rotary parts are contained in an oil bath in a strong heavy rolled section casing. A dual mechanical control (hand and pedal) allows processing in any adverse condition. The interchangeable blades have several shearing positions. The machines are also equipped with a magnetothermal switch with release coil and tap on the motor.

- EBC42 - Max Cutting Dia - 36mm
- EBC52 - Max Cutting Dia - 42mm

- Casing built in single cast iron block for a high degree of sturdiness and reliability
- Two stage cutting helps for Soft cut
- Equipped with a control lever, foot pedal and emergency stop button
- Blades with 4 cutting sides
- 4 wheels helps for easy transportation



HAND LEVER



EASY TRANSPORT



SAFETY GUARD

SPECIFICATION

Model	RPM	Power Supply	MOTOR KW HP	R 45 KG/MM ² 1ø 2ø 3ø	R 65 KG/MM ² 1ø 2ø 3ø	R 80 KG/MM ² 1ø 2ø 3ø	Dimension CM	Weight (kg)
EBC42	90	400V - 3P	3 - 4	42 25 12	36 20 10	32 16 08	120x75x91	680
EBC52	47	400V - 3P	3 - 4	52 32 20	42 25 16	36 20 12	130x71x94	770